












Product Information

Technical Data Sheet

Classification	ISO 10874 EN15468		Class 23 : Heavy Domestic Class 33 : Heavy Commercial	AC5
Length			1845	mm
Width			244	mm
Thickness			10	mm
Pack Size			1.3	m ²
Surface			Three-dimensional interlaced melamine resin	
Décor			Melamine Resin, Printed Décor	
Balance Film			Three-dimensional interlaced melamine resin	
Installation Type			Mechanical Locking Clic-System	
Residential Wear Warranty			30	Years
Commercial Warranty			5	Years

Technical Information

Fire Classification	EN13501		Hardly Flammable ~ B1	Cfl-s1
Emission	EN717-1		Lower than 0.05	ppm
Slip Resistance			Technical Class DS	
Thermal Conductivity	DIN EN 12667		R=0.075	m ² K/w
Resistance to Staining	EN 438-2		Grade 5 No Visible Change	
Locking Strength	ISO 24334		Fl 0.2 ≥ 1 Fs 0.2 ≥ 2	kN/m
Surface Layer Width	EN 13329		± 0.1	mm
Surface Layer Length	EN 13329		± 0.3	mm
Squareness	EN 13329		Max 0.2	mm
Surface Layer Straightness	EN 13329		<0.3	mm/m
Height Difference Between Elements	EN 13329		Max 0.15	mm
Openings Between Elements	EN 13329		Max 0.2	mm
Formaldehyde Content	EN 717-1		< 0.05	ppm



13
KDE_LF_008_EN_14041
2020



The mark of responsible forestry

