























**Product Information**
**Technical Data Sheet**

Norm	EN ISO 26986			
Intensity Of Use	ISO 10874 (EN 685)		<b>32 Heavy Commercial</b> <b>41 Industrial</b>	Class
Total Thickness	EN ISO 24346 (EN 428)		3.3mm	mm
Wear Layer	EN ISO 24340 (EN 429)		0.37 (PU Wear Layer)	mm
Abrasion Group	EN 660-2		T	Class
Total Weight	EN ISO 23997 (EN 430)		2270	g/m <sup>2</sup>
Standard Width	EN ISO 24341 (EN 426)		2 - 4	mtr
Standard Length	EN ISO 24341 (EN 426)		+/- 20	mtr
Commercial Warranty			5	Years
Cold Welding			Type A	

**Technical Information**

Dimensional Stability	EN ISO 23999 (EN 434)		≤ 0.40	%
Curling	EN ISO 23999		≤ 8	mm
Light Stability	EN ISO 105 B02		≥ 6	Degree
Residual Indent	EN ISO 24343-1 (EN 433)		≤ 0.20	mm
Impact Sound Improvement	EN ISO 717/2		△ Lw 20	dB
Dynamic Coefficient of Friction	EN 13893		> 0.6	
Slip Resistance	DIN 51130		R10	Scale
Reaction to Fire	EN 13501-01		Bfl-s1	Class
Underfloor Heating	EN 12667		Suitable	
Thermal Resistance	ISO 8302		0.032	m <sup>2</sup> K/w
Thermal Conductivity	EN 12524		0.10	W/m.k
Chemical Resistance	ISO 26987 (EN423)		Resistant	
Static Electrical Propensity	EN 1815		< 2kV	On Concrete
Determination of Peel Resistance	EN ISO 24345		≥ 50N/50mm	
Furniture Leg Resistance	ISO 16581 (EN424)		No Damage	
Castor Chair Resistance	EN ISO 4918		Suitable (Type Wheel H)	

**Environment**



- No heavy metals
- No solvents
- No Formaldehydes
- No harmful plasticizers

100% Recyclable.

Slovenian plant / Slovenian / Belgium plant

Certifié ISO 14001 / Certifié ISO 9001



100% phthalate free  
\*for all products produced from May 2017 onwards

EN 14041

**CE**

**05**

DOP: 450-SC0013-1  
B.I.G. Flooring nv, Rijksweg  
442 B - 8710, Wielsbeke, BELGIUM  
NB: 0534  
Resilient floor covering for use within building




**Powerful Bacterial Protection Built-in**

Our vinyl floors have bacteriostatic properties built-in and undergo severe testing to achieve ISO 846 standards. This demonstrates our dedication to give our customers total peace of mind.



BACTERIA RESISTANT  
INSTANT PROTECTION  
ISO 846

**E1**  
APPROVED FOR EMISSIONS

E1 means that the level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m<sup>3</sup> of air)

**g BB**

Ausschuss zur gesundheitlichen Bewertung von Bauprodukten

**floor score**

CERTIFIED BY SGS Global Services

ÉMISSIONS DANS L'AIR INTÉRIEUR

**A+**

A+ A B C