























## Product Information

## Technical Data Sheet

Norm	EN ISO 10582			
Intensity Of Use	ISO 10874 (EN 685)		<b>34</b> Very Heavy Commercial <b>43</b> Heavy Industrial	Class
Total Thickness	EN ISO 24346 (EN 428)		2mm	mm
Wear Layer	EN ISO 24340 (EN 429)		0.70 (PU Wear Layer)	mm
Abrasion Group	EN 660-2		T	Class
Total Weight	EN ISO 23997 (EN 430)		2800	g/m <sup>2</sup>
Standard Width	EN ISO 24341 (EN 426)		2 - 4	mtr
Standard Length	EN ISO 24341 (EN 426)		+/- 20	mtr
Commercial Warranty			5	Years
Hot Welding			Matching Weld Rods	

## Technical Information

Dimensional Stability	EN ISO 23999 (EN 434)		≤ 0.40	%
Curling	EN ISO 23999		≤ 8	mm
Light Stability	EN ISO 105 B02		≥ 6	Degree
Residual Indent	EN ISO 24343-1 (EN 433)		≤ 0.10	mm
Impact Sound Improvement	EN ISO 717/2		△ Lw 6	dB
Dynamic Coefficient of Friction	EN 13893		> 0.6	
Slip Resistance	DIN 51130		R10	Scale
Reaction to Fire	EN 13501-01		Bfl-s1	Class
Underfloor Heating	EN 12667		Suitable	
Thermal Resistance	ISO 8302		0.014	m <sup>2</sup> K/w
Thermal Conductivity	EN 12524		0.14	W/m.k
Chemical Resistance	ISO 26987 (EN423)		Resistant	
Static Electrical Propensity	EN 1815		< 2kV	On Concrete
Determination of Peel Resistance	EN ISO 24345		≥ 50N/50mm	
Furniture Leg Resistance	ISO 16581 (EN424)		No Damage	
Castor Chair Resistance	EN ISO 4918		Suitable (Type Wheel H)	

### Environment



100% Recyclable.

- No heavy metals
- No solvents
- No Formaldehydes
- No harmful plasticizers

Slovenian plant Slovenian / Belgium plant



100% phthalate free  
\*for all products produced from May 2017 onwards



Ausschuss zur gesundheitlichen Bewertung von Bauprodukten



EN 14041



05

DOP: 450-SC0013-1

B.I.G Flooring nv, Rijksweg  
442 B - 8710, Wielsbeke, BELGIUM

NB: 0534

Resilient floor covering for use within building



### Powerful Bacterial Protection Built-in

Our vinyl floors have bacteriostatic properties built-in and undergo severe testing to achieve ISO 846 standards. This demonstrates our dedication to give our customers total peace of mind.



**E1**  
APPROVED FOR EMISSIONS

E1 means that the level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m<sup>3</sup> of air)