
















Product Information


Technical Data Sheet

Intensity Of Use	ISO 10874 (EN 685)		23 High Domestic 32 Moderate Commercial	Class
Total Thickness	EN ISO 24346 (EN 428)		2.60	mm
Wear Layer	EN ISO 24340 (EN 429)		0.35 (PU Wear Layer)	mm
Abrasion Group	EN 660-2		T	Class
Total Weight	EN ISO 23997 (EN 430)		1800	g/m ²
Standard Width	EN ISO 24341 (EN 426)		2 - 4	mtr
Standard Length	EN ISO 24341 (EN 426)		+/- 20	mtr
Residential Warranty			15	Year

Technical Information

Impact Sound Improvement	EN ISO 717/2		△ Lw 18	dB
Dynamic Coefficient of Friction	EN 13893		DS	
Slip Resistance	DIN 51130		R11	Scale
Reaction to Fire	EN 13501-01		Cfl-s1	Class
Underfloor Heating	EN 12667		Suitable	
Thermal Resistance	ISO 8302		0.0104	m ² K/w
Thermal Conductivity	EN 12524		0.25	W/m.k
Chemical Resistance	ISO 26987 (EN423)		Resistant	

67844-67848



E1
APPROVED FOR EMISSIONS

E1 means that the level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m³ of air)

Environment



100% Recyclable.

- No heavy metals
- No solvents
- No Formaldehydes
- No harmful plasticizers

ÉMISSIONS DANS L'AIR INTÉRIEUR*



A+

A+ A B C