





















## Product Information

## Technical Data Sheet

Intensity Of Use	ISO 10874 (EN 685)		23 High Domestic 31 Moderate Commercial	Class
Total Thickness	EN ISO 24346 (EN 428)		2.0	mm
Wear Layer PUR Surface Treatment	EN ISO 24340 (EN 429)		0.30	mm
Abrasion Group	EN 660-2		T	Class
Total Weight	EN ISO 23997 (EN 430)		3900	g/m <sup>2</sup>
Plank Size	EN ISO 24342		180 x 1200	mm
Tile Size	EN ISO 24342		300 x 600	mm
Box Planks			4.75m <sup>2</sup>	22 Planks
Box Tiles			4.86m <sup>2</sup>	27 Tiles
Residential Warranty			25	Year
Commercial Warranty			7	Year

## Technical Information

Dimensional Stability	EN ISO 23999 (EN 434)		Average ≤ 0.10	%
Curling	EN ISO 23999		≤ 2.0	mm
Light Stability	EN ISO 105 B02		≥ 6	Degree
Residual Indent	EN ISO 24343-1 (EN 433)		≤ 0.10	mm
Impact Sound Improvement	EN ISO 717/2		△ Lw 3	dB
Dynamic Coefficient of Friction	EN 13893		DS	
Slip Restraint	DIN 51130		R9	Scale
Reaction to Fire	EN 13501-01		Bfl-s1	Class
Underfloor Heating	EN 12524		Suitable Max 29°	
Thermal Resistance	ISO 8302		0.0042	m <sup>2</sup> K/w
Squareness	EN ISO 24342		≤ 0.35	mm
Straightness	EN ISO 24342a		≤ 0.35	mm
Stain Resistance	ISO 26987 (EN423)		Resistant / Very Good	
Electrical Resistance	EN 1081		≤ 10 <sup>9</sup> Ohm	On Concrete
Furniture Leg Resistance	ISO 16581 (EN424)		No Damage	
Castor Chair Resistance	EN ISO 4918		No Change	Wear Layer

