






















Product Information

Technical Data Sheet

Norm	EN ISO 26986			
Intensity Of Use	ISO 10874 (EN 685)		23 High Domestic 31 Moderate Commercial	Class
Total Thickness	EN ISO 24346 (EN 428)		4.00	mm
Wear Layer	EN ISO 24340 (EN 429)		0.25	mm
Abrasion Group	EN 660-2		T	Class
Total Weight	EN ISO 23997 (EN 430)		2450	g/m ²
Standard Width	EN ISO 24341 (EN 426)		2 - 3 - 4	mtr
Standard Length	EN ISO 24341 (EN 426)		+/- 20	mtr
Residential Warranty			15	Year

Technical Information

Dimensional Stability	EN ISO 23999 (EN 434)		≤ 0.40	%
Curling	EN ISO 23999		≤ 8	mm
Light Stability	EN ISO 105 B02		≥ 6	Degree
Residential Indent	EN ISO 24343-1 (EN 433)		≤ 0.35	mm
Impact Sound Improvement	EN ISO 717/2		△ Lw 17	dB
Dynamic Coefficient of Friction	EN 13893		> 0.6	
Slip Resistance	DIN 51130		R10	Scale
Reaction to Fire	EN 13501-01		Bfl-s1	Class
Underfloor Heating	EN 12667		Suitable	
Thermal Resistance	ISO 8302			m ² K/w
Thermal Conductivity	EN 12524			W/m.k
Chemical Resistance	ISO 26987 (EN423)		Resistant	
Static Electrical Propensity	EN 1815		< 2kV	On Concrete
Determination of Peel Resistance	EN ISO 24345		≥ 50N/50mm	
Furniture Leg Resistance	ISO 16581 (EN424)		No Damage	
Castor Chair Resistance	EN ISO 4918		Suitable (Type Wheel H)	

Environment



100% Recyclable.

- No heavy metals
- No solvents
- No Formaldehydes
- No harmful plasticizers



100% phthalate free
*for all products produced
from May 2017 onwards

Slovenian plant Slovenian / Belgium plant



E1
APPROVED
FOR
EMISSIONS

E1 means that the level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m³ of air)



CERTIFIED BY
SCS Global Services

