














Product Information

Technical Data Sheet

Intensity Of Use	ISO 10874 (EN 685)		34 Very Heavy Commercial 43 Heavy Industrial	Class
Total Thickness	EN ISO 24346 (EN 428)		2.00	mm
Total Weight	EN ISO 23997 (EN 430)		2430	g/m2
Standard Width	EN ISO 24341 (EN 426)		2	mtr
Standard Length	EN ISO 24341 (EN 426)		+/- 20	mtr
Commercial Warranty			10	Years
European Norm For Safety Flooring	EN13845		Conforms	

Technical Information

Light Stability	EN ISO 105 B02		≥ 6	Degree
Dynamic Coefficient of Friction	EN 13845		> 0.36	
Slip Resistance	AS/NZS 4586		R10	Scale
Reaction to Fire	EN 13501-01 (E648)		Bfl-s1	Class
Underfloor Heating	EN 12667		Suitable	
Chemical Resistance	ISO 26987 (EN423)		Good Resistance	
Static Electrical Propensity	EN 1815		< 2kV	On Concrete
Castor Chair	ISO 4918		OK	

HSE Compliant

36+

Pendulum Wet Test

Sustainable Slip Resistance
throughout product's guaranteed life



100% RECYCLABLE
CONTAINS RECYCLED MATERIAL

A+BRE
ENP 472
ENVIRONMENTAL
RATING

THIRD-PARTY VERIFIED
EPD
ISO 14025 and EN 15804

Recofloor™
Vinyl Take-Back Scheme

