

















Product Information

Technical Data Sheet

Classification	ISO 10874 EN15468	 	Class 23 : Heavy Domestic Class 32 : Moderate Commercial	AC4
Length			1291	mm
Width			193	mm
Thickness			10	mm
Pack Size			1.74	m ²
Installation Type			Mechanical Locking Clic-System	
Residential Wear Warranty			20	Years
Commercial Warranty			5	Years
Total Weight			16.48	Kg

Technical Information

Fire Classification	EN13501		Hardly Flammable ~ B1	Cfl-s1
Emission			Lower than 0.05	ppm
Slip Resistance			Technical Class DS	
Thermal Conductivity	DIN EN 12667		R=0.08	m ² K/w
Impact Resistance	EN 13329		Small Ball ≥ 12N Big Ball ≥ 750mm	
Antistatic Properties	EN1815		Yes < 2	kV
Resistance to Staining	EN 438-2		Group 1 + 2: Level 5 Group 3: Level 4	
Surface Soundness	EN13329, Annex D		> 1.25	N/mm ²
Surface Layer Width	EN 13329		± 0.1	mm
Surface Layer Length	EN 13329		± 0.5	mm
Thickness	EN 13329		± 0.5	mm
Thickness Swelling	ISO 24336		≤ 18	%
Effect of Furniture Leg	EN 424		No damage shall be visible, when tested with foot type 0 artefact	
Effect of castor chair	EN 425 (Type W)		No change in appearance or damage	

