















Product Information

Technical Data Sheet

Classification	ISO 10874 EN15468		Class 23 : Heavy Domestic Class 31 : Light Commercial	AC3
Length			1291	mm
Width			192	mm
Thickness			7	mm
Pack Size			2.48	m ²
Installation Type			Mechanical Locking Clic-System	
Residential Wear Warranty			15	Years
Total Weight			16.3	Kg

Technical Information

Fire Classification	EN13501		Hardly Flammable ~ B1	Cfl-s1
Emission			Lower than 0.05	ppm
Slip Resistance			Technical Class DS	
Thermal Conductivity	DIN EN 12667		R=0.06	m ² K/w
Impact Resistance	EN 13329		Small Ball ≥ 8N Big Ball ≥ 500mm	
Antistatic Properties	EN1815		Yes < 2	kV
Resistance to Staining	EN 438-2		Group 1 + 2: Level 5 Group 3: Level 4	
Surface Soundness	EN13329, Annex D		> 1.0	N/mm ²
Surface Layer Width	EN 13329		± 0.1	mm
Surface Layer Length	EN 13329		± 0.5	mm
Thickness	EN 13329		± 0.5	mm
Thickness Swelling	ISO 24336		≤ 18	%
Effect of Furniture Leg	EN 424		No damage shall be visible, when tested with foot type 0 artefact	
Effect of castor chair	EN 425 (Type W)		No change in appearance or damage	

