



















## Product Information

## Technical Data Sheet

Intensity Of Use	ISO 10874 (EN 685)		<b>23</b> Heavy Domestic <b>32</b> Moderate Commercial	Class
Total Thickness	EN ISO 24346 (EN 428)		2.40	mm
Wear Layer	EN ISO 24340 (EN 429)		0.35	mm
Total Weight	EN ISO 23997 (EN 430)		1580	g/m <sup>2</sup>
Standard Width	EN ISO 24341 (EN 426)		2, 3, 4	mtr
Standard Length	EN ISO 24341 (EN 426)		+/- 20	mtr
Residential Warranty			20	Years

## Technical Information

Dimensional Stability	EN ISO 23999 (EN 434)		≤ 0.20	%
Light Stability	EN ISO 105 B02		≥ 6	Degree
Residual Indent	EN ISO 24343-1 (EN 433)		≤ 0.20	mm
Impact Sound Improvement	EN ISO 717/2		△ Lw 16	dB
Formaldehyde Emission	EN 717-1		E1 HCHO	
Slip Resistance	DIN 51130		R10	Scale
Reaction to Fire	EN 13501-01		Cfl-s1	Class
Underfloor Heating	EN 12667		Suitable	
Thermal Resistance	ISO 8302		0.03	m <sup>2</sup> K/w
Chemical Resistance	ISO 26987 (EN423)		Resistant	
Static Electrical Propensity	EN 1815		< 2kV	On Concrete
Castor Chair	ISO 4918		OK	

