






















## Product Information

## Technical Data Sheet

|                     |                       |  |   |                  |
|---------------------|-----------------------|--|---|------------------|
| Norm                | EN 13845 / 13553      |  |   |                  |
| Intensity Of Use    | ISO 10874 (EN 685)    |  | <b>34</b> Very Heavy Commercial<br><b>43</b> Heavy Industrial | Class            |
| Total Thickness     | EN ISO 24346 (EN 428) |   | 2mm   | mm               |
| Wear Layer          | EN ISO 24340 (EN 429) |   | 0.9   | mm               |
| Total Weight        | EN ISO 23997 (EN 430) |   | 2500  | g/m <sup>2</sup> |
| Standard Width      | EN ISO 24341 (EN 426) |   | 2   | mtr              |
| Standard Length     | EN ISO 24341 (EN 426) |   | +/- 20  | mtr              |
| Commercial Warranty |                       |   | 5   | Years            |
| Hot Welding         |                       |  | Matching Weld Rods  |                  |

## Technical Information

|                                 |                         |   |  |                    |
|---------------------------------|-------------------------|---|--|--------------------|
| Light Stability                 | EN ISO 105 B02          |    | ≥ 6  | Degree             |
| Residual Indent                 | EN ISO 24343-1 (EN 433) |   | ≤ 0.10                                     | mm                 |
| Impact Sound Improvement        | EN ISO 717/2            |  | Lw 4                                       | dB                 |
| Dynamic Coefficient of Friction | EN 13893                |  | DS   |                    |
| Slip Resistance                 | DIN 51130               |  | △10  | Scale              |
| Reaction to Fire                | EN 13501-01             |  | Bfl-s1                                     | Class              |
| Underfloor Heating              | EN 12667                |  | Suitable                                   |                    |
| Thermal Resistance              | ISO 8302                |  | 0.014                                      | m <sup>2</sup> K/w |
| Thermal Conductivity            | EN 12524                |  | 0.14                                       | W/m.k              |
| Chemical Resistance             | ISO 26987 (EN423)       |  | Resistant                                  |                    |
| Static Electrical Propensity    | EN 1815                 |  | < 2kV                                      | On Concrete        |
| Wear Resistance                 | EN13845                 |  | ≤ 10% Particles lost over<br>50,000 cycles |                    |
| Furniture Leg Resistance        | ISO 16581 (EN424)       |  | No Damage                                  |                    |
| Castor Chair Resistance         | EN 425                  |  | Pass                                       |                    |

