




















Product Information

Technical Data Sheet

| | | | | |
|----------------------|-----------------------|--|--|------------------|
| Norm | EN ISO 26986 | | | |
| Intensity Of Use | ISO 10874 (EN 685) |  | 23 High Domestic 31 Moderate Commercial | Class |
| Total Thickness | EN ISO 24346 (EN 428) |  | 2.5 | mm |
| Wear Layer | EN ISO 24340 (EN 429) |  | 0.25 | mm |
| Abrasion Group | EN 660-2 |  | T | Class |
| Total Weight | EN ISO 23997 (EN 430) |  | 1550 | g/m ² |
| Standard Width | EN ISO 24341 (EN 426) |  | 2-3-4 | mtr |
| Standard Length | EN ISO 24341 (EN 426) |  | +/- 20 | mtr |
| Residential Warranty | | | 12 | Year |

Technical Information

| | | | | |
|---------------------------------|-------------------------|---|-----------|--------------------|
| Dimensional Stability | EN ISO 23999 (EN 434) |  | ≤ 0.40 | % |
| Curling | EN ISO 23999 | | ≤ 8 | mm |
| Light Stability | EN ISO 105 B02 |  | ≥ 6 | Degree |
| Residual Indent | EN ISO 24343-1 (EN 433) |  | ≤ 0.35 | mm |
| Impact Sound Improvement | EN ISO 717/2 |  | △ Lw 16 | dB |
| Dynamic Coefficient of Friction | EN 13893 |  | > 0.6 | |
| Slip Resistance | DIN 51130 |  | R10 | Scale |
| Reaction to Fire | EN 13501-01 |  | Bfl-s1 | Class |
| Underfloor Heating | EN 12667 |  | Suitable | |
| Thermal Resistance | ISO 8302 |  | 0.025 | m ² K/w |
| Thermal Conductivity | EN 12524 |  | 0.10 | W/m.k |
| Chemical Resistance | ISO 26987 (EN423) |  | Resistant | |
| Static Electrical Propensity | EN 1815 |  | < 2kV | On Concrete |

Environment



100% Recyclable.

- No heavy metals
- No solvents
- No Formaldehydes
- No harmful plasticizers



100% phthalate free
*for all products produced
from May 2017 onwards

Slovenian plant

Slovenian / Belgium plant



E1

APPROVED FOR EMISSIONS

E1 means that the level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m³ of air)



CERTIFIED BY SCS Global Services

